



## SCHEMA TECNICA PANNELLI ALLUMINIO

Supporto in Pyral

### Tipo B

**PANNELLI MONOFACCIA PER PORTE BLINDATE**  
Misure standard: 110x230 e 55x230  
Spessore standard **7 mm**.  
Spessori maggiorati: 9.5, 12 mm  
Spessori ridotti: 4, 5, 6 mm con bordi ribassati solo su pannelli a misura

**MONO-SIDE PANELS FOR ARMoured DOORS**  
Standard dimension: 110x230 and 55x230  
Standard Thickness: **7 mm**  
Oversize thickness: 9.5, 12 mm  
Reduced thickness: 4, 5, 6 mm with reduced edge only on panels to measure.

termoisolante

Supporto in mdf

### Tipo R

**PANNELLI MONOFACCIA PER PORTE BLINDATE**  
Misure standard: 110x230 e 55x230  
Misure maggiorate: 110x250 e 55x250  
Misure ridotte: 95x215  
Spessore standard **7 mm**.  
Spessori maggiorati: 9.5, 12 mm  
Spessori ridotti : 4, 5, 6 mm con bordi ribassati solo su pannelli a misura

**MONO-SIDE PANELS FOR ARMoured DOORS**  
Standard dimension: 110x230 and 55x230  
Oversize dimension: 110x250 and 55x250  
Reduced dimension: 95x215  
Standard Thickness: **7 mm**  
Oversize thickness: 9.5, 12 mm  
Reduced thickness: 4, 5, 6 mm with reduced edge only on panels to measure.



*Industrial*

